

Production Equipment 2500-UC

Galvanized Top - Undercounter

Self-contained



2562-UC shown with options

SPECIFICATIONS:

TOP: Corrosion resistant metal enamel finish turned down on four sides and welded integrally to base

EXTERIOR: Back and bottom of 20 GA steel with painted enamel finish, Body supported by 14 GA galvanized steel box channels for casters, Ends of 20 GA stainless steel, type 304-#4 finish, integrally welded to top

INTERIOR: Bottom, Back, and Top of 22 GA stainless steel type 304-#2B finish, sides of one-piece high impact plastic

INSULATION: Rigid Polyurethane Foam

DOOR JAMS: One-piece high-impact plastic with concealed magnets on perimeter for positive sealing

DOORS: Exterior of one-piece die-stamped 22 GA stainless steel type 304-#4 finish, Interior of high-impact plastic, Gasket mounted w/ aluminum strips and screws for easy removability and to ensure a proper seal, Doors mounted on 12 GA spring-loaded self-closing hinges, Stainless handle with stamped grip

SHELVES: One, removable heavy-steel frame vinyl-coated shelf, per door

CASTERS: (Standard) Removable 6 1/4" high with 5" diameter wheels, front casters include brakes

REFRIGERATION: Unit has a high-temperature balanced system using a hermetically sealed condenser. Forced-air evaporator with protective-coated coil and expansion valve, System comes assembled with cord and 5-15-P plug, base tested to operate between 36 and 40 degrees F

ITEM # _____

PROJECT _____

DATE _____

MODEL	DIM
2562-UC	62"L x 31"D
2586-UC	86"L x 31"D
2510-UC	110"L x 31"D

FEATURES

- Self-contained unit
- Stainless steel ends
- Condensate Evaporator
- 6-1/4" swivel casters
- Self-closing hinges
- (1) Wire shelf per door

OPTIONS

- Legs in lieu of casters
- Bun pan racks to hold 18" x 26" bun pans (pans by others)
- Drawers in lieu of door
- Stainless steel back

Production Equipment 2500-UC
Galvanized Top - Undercounter
Self-contained



2562-UC



2586-UC



2510-UC

OPTIONS

Removable Bun Pan Racks
In place of (1) shelf per door



Refrigerated Drawers
Two drawers replace 1 door



STATISTICAL DATA

MODEL	LGTH	SHELVES PER UNIT	CONDENSING UNIT	VOLTS/ CYCLE/ PHASE	TOTAL AMPS	NEMA PLUG	SHIP WT.
2562-UC	62"	2	1/4-HP R-134A	115v/60/1	8.38	5-15-P	325#
2586-UC	86"	3	1/3-HP R-134A	115v/60/1	10.78	5-15-P	513#
2510-UC	110"	4	1/3-HP R-134A	115v/60/1	11.42	5-15-P	635#

MECHANICAL DATA

Production Equipment 2500 Series

C Condensing unit wired to junction box 22" AFF, rear of condenser compartment is open for cord to exit 115V/60/1

S On/off switch 22" AFF with 8 foot cord and plug 5-15-P

D 5/8" OD copper drain for condensate evaporator 12 1/2" AFF

SECTION VIEW

