Modular Equipment 20000 Series

Freezer Bases - Stainless Steel Top
Self-contained

ITEM # _____

PROJECT _____

_____

_____

DATE _____

MODEL	LENGTH
L-20138	38"
L-20150	50"
L-20156	56"
L-20162	62"
L-20168	68"
L-20174	74"
L-20180	80"
L-20186	86"

DEPTH
23", 28" OR 32"



L-20162 shown with options

SPECIFICATIONS:

TOP: Die-formed construction of one-piece 16 GA stainless steel type 304-#4 finish with 2 5/8" nosing, Backsplash to be 3/8" coved, 6" high x 2 1/8" wide, Sheared ends fitted with recessed 12 GA steel bars for adjoining units, producing a hairline seam

EXTERIOR: Back, bottom, and sides of 20 GA steel with painted enamel finish, Body supported by 14 GA galvanized steel box channels for legs

CONDENSER HOUSING: Fitted with a stainless steel snap-on louvered panel

INTERIOR: Bottom and Back of 22 GA stainless steel type 304-#2B finish, sides of one-piece high impact plastic, Top of aluminum

DOOR JAMS: One-piece high-impact plastic with concealed magnets on perimeter for positive sealing, w/ door jam heaters to prevent gasket freezing

DOORS: Exterior of one-piece die-stamped 22 GA stainless steel type 304-#4 finish, Interior of high-impact plastic, Gasket mounted w/ aluminum strips and screws for easy removability and to ensure a proper seal, Doors mounted on 12 GA spring-loaded self-closing hinges, Stainless handle with stamped grip

SHELVES: One, removable heavy-steel frame epoxy-coated shelf per door

LEGS: 8" high legs standard, 1 5/8" tubing welded to steel plate and fastened to body support channels, Bullet-foot has 1 1/8" of adjustment, All legs are stainless steel

REFRIGERATION: Self-contained unit has a low-temperature balanced system using a hermetically sealed condenser, Forced-air evaporator with protective-coated coil, expansion valve, defrost heater, and timer, System comes assembled with cord and 5-15-P or 5-20-P plug, Base tested to operate between -5 and 0 degrees F

FEATURES


- Available with other modular equipment under one top up to 10 feet in length
- 16 GA reinforced top
- Self-contained unit
- Self-closing doors
- (1) Wire shelf per door
- Refrigeration system has expansion valve & temp. control for rapid recovery
- Uniform integration in design, quality and parts
- Includes defrost heaters, defrost timer

OPTIONS


- Casters (specify working height)
- Compressor Left
- Drawers
- Custom Lengths

Modular Equipment L-20000 Series - S/S Work Top


DIMENSIONAL DATA




L-20138




L-20156




L-20168




L-20180




L-20150




L-20162




L-20174



L-20186







STATISTICAL DATA

MODEL	LGTH	CAP. CU. FT.			SHELVING (SQ FT)				CONDENSING UNIT [ii]	VOLTS/ CYCLE/ PHASE	TOTAL AMPS [iii]	NEMA PLUG	SHIP WT.
		23"	28"	32"	23"	28"	32"	# PER UNT					
L-20138	38"	3.9	4.6	5.6	4.5	5.9	7.0	1	1/4-HP R-404	115v/60/1	7.15	5-15-P	375#
L-20150	50"	5.8	7.8	9.4	7.3	9.5	11.3	2	1/4-HP R-404	115v/60/1	7.15	5-15-P	405#
L-20156	56"	6.9	9.3	11.2	8.6	11.3	13.4	2	1/3-HP R-404	115v/60/1	10.1	5-15-P	445#
L-20162	62"	8.1	10.9	13.1	10.0	13.1	15.5	2	1/3-HP R-404	115v/60/1	10.1	5-15-P	485#
L-20168	68"	9.4	12.5	15.0	11.4	14.8	17.6	3	1/3-HP R-404	115v/60/1	10.45	5-15-P	515#
L-20174	74"	10.6	14.1	16.9	12.7	16.6	19.7	3	1/2-HP R-404	115v/60/1	13.35	5-20-P	545#
L-20180	80"	11.6	15.5	18.6	14.1	18.4	21.8	3	1/2-HP R-404	115v/60/1	13.35	5-20-P	580#
L-20186	86"	12.8	17.1	20.5	15.5	20.2	24.0	3	1/2-HP R-404	115v/60/1	13.35	5-20-P	615#


Standard
Self-closing Doors



Optional
Refrigerated Drawers



Optional
26" Refrigerated Drawers
(adds 2" to unit length)



shown w/ optional
full extension drawer slides

Notes:
i. Compressor left available
ii. Custom units may require modified BTU ratings and/or condensing unit HP
iii. Optional hot gas condensate evaporator is factory recommended, if electric evaporator is required, add 0.39 AMP to total

Modular Equipment 20000 Series MECHANICAL DATA

(C) Condensing unit wired to junction box 24" AFF, rear of condenser compartment is open for cord to exit 115V/60/1

S On/off switch 24" AFF with 8 foot cord and plug 5-15-P

D 5/8" OD copper drain for condensate evaporator 14 1/2" AFF

T Defrost Timer 24" AFF hard-wired to J-Box

